















## TMC 7200 SERIES

integrated Handy POS tablet by AURES

### 7" Mobile POS

Available in 2 different references, this 7" Mobile POS series offers stylish exclusive design, high performance and low power consumption; it is an ideal tablet in all points of service, especially in the catering and hospitality environments, where its light weight and compact dimensions will optimise its many functionalities.

This ruggedized POS tablet is designed specifically for point of service use, and especially the catering and hospitality sectors. Available in 7" sleek LCD, the TMC 7200 series is very light weight but retail hardened, and can be dropped from up to 1.2 m four (about 4 feet).

Additionally, the Intel Atom CPU enables the device to support Windows 10 IoT Enterprise allowing effortlessly handled CPU heavy applications.

The Quad Core fanless processor(s) allow for ultralow power consumption and quick speed.

A 4 or 8 hour battery life allows for use with no recharging made necessary. The TMC 7200 feature WIFI, Bluetooth and NFC; 2D Barcode, MSR and smart card readers are an option.



Available with 2 types of anti-fall straps, it will be your mobility best partner on the POS, offering both landscape and portrait data display.







# TMC 7200 SERIES

Exclusive, elegant and slim design

High performance and low energy consumption

High capacity batteries

7" LCD screen with PCAP touch - 800 x 1280 resolution

Multifunction applications (supports 2D barcode readers, MSR, Smart Card readers WIFI, Bluetooth and NFC)

Resists drops from 1.20m (4 feet)

IP 54 standardised front panel

Windows 10 IoT Enterprise compatible

Optional handstrap for both portrait and landscape use

MODEL

Processor



| Ma |  |
|----|--|
|    |  |
|    |  |







|                        | (up to 2.40 GHz)  |
|------------------------|---|
| Memory RAM             | LPDDR3 4GB  |
| Memory Flash           | eMMC 64GB   |
| Power requirement      | DC 12V  |
| Display                | 7" IPS / LCD panel Portrait & Landscape mode (30.000 hours) |
| Brightness             | 400 cd/m <sup>2</sup>                                       |
| Resolution             | 800 x 1280  |
| Vibrator               | yes   |
| G-sensor               | yes   |
| WIFI & Bluetooth       | 802.11 b/g/n, Bluetooth 4.0                                 |
| Barcode scanner        | 2D barcode scanner (optional)                               |
| NFC                    | NXP NPC300 (optional)                                       |
| MSR Smart Card Reader  | ISO 7816 & EMV level 1 & 2 certification (optional)         |
| Net weight             | 415 g (4h battery) - 470 g (8h battery)                     |
| Dimensions (W x H x D) | 118 x 192 x 26 mm   |
| Certifications         | FCC/CE/RCM  |
| OS                     | Windows 10 IOT LTSC 2019 64bit                              |

### TABLET I/O PORTS

| SD                | Micro SD up to 128GB                        |
|-------------------|---|
| USB               | For MSR only                                |
| Cradle connectors | POGO pin for charging and data transmission |

**TMC 7200** 

Atom x5-Z8550 Quad Core

| BATTERY             | 4 HOURS  | 8 HOURS                  |
|---------------------|----------|--------------------------|
| Capacity            | 3700 mAh | 7400 mAh                 |
| Operation time      | 4 hours  | 8 hours (standard JEITA) |
| Charging time (OFF) | 3 hours  | 5 hours                  |
|                     |          |                          |

| CRADLE(S) SPECIFICATIONS      | TMC 7200               |
|-------------------------------|------------------------|
| Kensington Security Lock Slot | 1                      |
| AC Power Adapter              | 12 Vdc/ 5 A / 60 W     |
| Tablet connector              | POGO pins (1 x 6 pins) |
| USB ports                     | Type A USB 2.0         |
| Net weight                    | 200g                   |
| Dimensions (Lx W x D)         | 179 x 135.3 x 55 mm    |
|                               |                        |

| FNV | RO | NM | FNT |
|-----|----|----|-----|

| Temperature (in operation) | 0 ~ 35°C (32°~95°F)      |
|----------------------------|--------------------------|
| Temperature (storage)      | -20° ~ 60°C (-4 ~ 140°F) |
| Humidity                   | 10 ~ 95%                 |
| Drop test                  | 1.2 m                    |
| Protection                 | IP54 front panel         |

### ADDITIONAL OPTIONS AND OTHERS

4 slots cradle, belt bag - holster, rotative handstrap, rubber spring cord

